

MORBARK® 23X CHIPARVESTOR®

FEATURES

- » The hydraulic chipper hood allows for easy knife access, while the 23" (58.42 cm) chipping diameter tackles some of the larger trees. With its 75" (190.5 cm) chipper disc, the 23X is able to chip large volumes of wood
- » 75" (190.5 cm) diameter x 5" (12.7 cm) thick three-knife chipper disc with LH rotation
- » Two-wheel hydraulic feed system: One 35" x 56" (88.9 cm x 142.24 cm) top feed wheel and one 13" x 56" (33.2 x 142.24 cm) bottom feed wheel
- » Large work platform for general chipper disc maintenance
- » Integrated Skidder Bar
- » Remote control with a tethered remote back-up system
- » Morbark Integrated Control Systems (MICS) diagnostic system monitors pressures, temperatures, clutch systems and engine efficiency to maximize performance
- » Reversing fan
- » Dirt separator with deflector
- » Hydraulic swivel/telescoping discharge spout
- » 11-HP (8.2 kW) air compressor
- » Light package
- » Rear hydraulic stabilizers

OTHER SPECIFICATIONS

- » Chip size: 5/8", 3/4", 7/8", 1" (mm: 15.88, 19, 22.22, 25.4)
- » Knives (3): 23" x 5" x 1/2" (58.42 cm x 12.7 cm x 1.27 cm)

OPTIONS

- » 4-Knife disc in lieu of standard 3-knife
- » ESPAR heating system for cold-weather start



Each disc is fabricated from plate steel and put through ultrasonic testing

Unrestricted infeed with dual feed wheel

Platform for general chipper disc maintenance



SPECIFICATIONS

US

METRIC

Chipping Capacity	23"	58.42 cm
Length	33'8"	10.26 m
Height	12'10"	3.91 m
Width	8'6"	2.59 m
Gross Weight	58,040 lb	26,326 kg
Tandem Weight	44,000 lb suspension (19,958 kg)	
Engine	CAT	
Horsepower	800 HP	596 kW
Fuel Capacity (tank)	300 gallons	1,135 litres
Hydraulic Oil	100 gallons	378 litres
Tires	(4) 385/65R/22.5 20-ply Super Singles	
Brakes	Air	
Towing arrangement	Fifth Wheel	
Tracks	Optional	



www.morbark.com

800.831.0042

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS

9/21/18